




(+) Other Pictures



Features

- Onboard Intel® Arrandale LV/ ULV CPU
- Intel® QM57 Chipset
- One 204-pin SODIMM Up to 4GB DDR3 800/ 1066 SDRAM
- Dual View, Dual-channel LVDS, DVI-I
- Dual Intel® Gigabit Ethernet
- 1 CF, 4 SATA, 2 COM, 8 USB, 16-bit GPIO
- Options: Express Card/34mm, Built-in Touch Screen
- Support iAMT 6.0
- Support RAID 0/ 1/ 5/ 10

Specifications

System

CPU	Onboard Intel® Arrandale LV/ ULV CPU
BIOS	Award 8 Mbit Flash BIOS
System Chipset	Intel® QM57
I/O Chip	Winbond W83627DHG-P
System Memory	One 204-pin SODIMM Socket Supports up to 4GB
SSD	One CompactFlash Type I/II Socket
Watchdog Timer	Reset: 1sec. ~ 65535min. and 1sec. or 1min./step
Expansion	One Express Card/ 34mm Slot (Optional)

I/O

MIO	1 x EIDE, 2 x SATA, 1 x KB & Mouse, 1 x RS-232, 1 x RS-232/ 422/ 485
IrDA	115Kbps, IrDA 1.0 Compliant
USB	8 x USB 2.0
DI/O	8-bit GPI, 8-bit GPO

Display

Chipset	Intel® QM57
Resolution	DVI Mode: 1920 x 1536 @ 75Hz (DVI-I), LCD/ Simultaneous Mode : 1600 x 1200 @ 75Hz
LVDS	Dual-channel 18/ 24-bit LVDS
Multiple Display	DVI + LVDS

Built-in Touch Screen (Optional)

Chipset	PenMount 6000
Touch Screen Interface	With 9-pin 2.0mm Box Header (Can be Selected to Support 4/ 5/ 8-wire Touch Screen)

Audio

Chipset	Realtek ALC883 Supports 5.1-CH Audio
Audio Interface	Mic-in, Line-in, Line-out

Ethernet

LAN	1 x Intel® 82577LM (Gigabit PHY), 1 x Intel® 82574L
Ethernet Interface	1000 Base-Tx Gigabit Ethernet Compatible

Mechanical & Environmental

Power Requirement	+12 V
ACPI	Single Power ATX Support S0, S3, S4, S5, ACPI 1.0b and 2.0 Compliant
Power Type	AT / ATX
Operation Temperature	0~60°C (32~140°F)
Operating Humidity	0%~90% relative humidity, non-condensing
Size (L x W)	4.5" x 6.5" (115 mm x 165 mm)
Weight	0.4 lbs (0.18 kg)

* Product specifications are subject to change without notice. Last update: 01/08/2010