

# GPP 10 Office

## Technical data:


**AC-Input:** 100 to 240 VAC (50 to 60 Hz)

**DC-Output:**

Output data	P/N
5V / 1600mA	1827490
6V / 1400mA	1827491
7,5V / 1200mA	1827492
9V / 1000mA	1827493
12V / 800mA	1827494
15V / 700mA	1827495
18V / 560mA	1827496
24V / 420mA	1827497

- Higher efficiency = higher power from same unit size
- New Design = conforms to the most important safety standards
- Complies with IEC 60950
- Interchangeable primary adapters
- Constant voltage, current limited
- Low standby power  $\leq 0,3$  Watt at  $U_{out}$  5V till 12V  
 $\leq 0,5$  Watt at  $U_{out}$  15V till 24V
- Continuously short circuit proof

./..



## GPP 10 Office

### Interchangeable primary adapters:

Adapter	P/N
Euro	1827417
UK	1827420
USA	1827422
AUS	1827425
IEC	1827428

### Application:

- Office machines
- Data transmission devices
- IT equipment
- Measurement and weighing technology

### Comparison between GPP and MPP system:

- Simple handling and audible snap-in of primary adapters
- Improved design of housing and primary adapters
- Fulfils most of the important international safety standards
- Fulfils Energy Star requirements