

MARSCHNER-RINGKERN-PROGRAMM

Toroidal core transformer



Typ/Type

Nennleistung/Power

Primär/Primary

Ringkerne 50-500VA 230 V~

Sicherheitstrafo
nach EN 61558
UL 506 / CSA
Temperaturklasse ta 70° C/B
IP00
Thermosicherung 120°C
KLASSE B
freie Enden 130mm lang

Safety transformer
nach EN 61558
UL 506 / CSA
Temperature class ta 70° C/B
IP00
Thermoswitch 120°C
CLASSE B
free ends 130mm lengths



Bestell Nr. Order No.	Leistung [VA] Power	Sekundär [V] Secondary	Strom [A] Current	Abmessungen D * H	Gewicht [Kg] Weight
R88.36/05038*	50	12	4,20	88 36	0,65
R93.38/05039*	60	12	5,00	93 38	0,91
R101.38/05040*	80	12	6,70	101 38	1,27
R110.40/05041*	100	12	8,40	110 40	1,34
R112.43/05042*	120	12	10,00	112 43	1,40
R101.48/05043*	150	12	12,50	101 48	1,56
R120.48/05044*	180	12	15,00	120 48	2,00
R103.53/05045*	200	12	16,70	103 53	2,10
R108.54/05046*	250	12	20,90	108 54	2,25
R113.55/05047*	300	12	25,00	113 55	2,75
R119.55/05048*	400	12	33,40	119 55	3,40
R128.60/05049*	500	12	41,70	128 60	4,00

Spezifische Kundenwünsche auf Anfrage (z.B. Kabel mit Stecker)
Specific customer requests available on enquiry (for example: wire with connector)

* keine Lagerware

* not available ex stock