



SocketModem® Embedded Analog Modems

Key Features:

- Complete data/fax modem solution including the controller, data pump, and DAA
- Space efficient universal socket connectivity
- Telecom approved in more than 50 countries
- V.92/56K bps and below data rates
- V.34/33.6K fax
- V.44 and V.42bis data compression
- V.42 error correction
- U.S. Caller ID reporting
- Low power/sleep mode
- Flash memory for easy updates
- V.22bis Fast Connect
- V.80 Synchronous Access
- Leased (dry) line operation
- 10 or 11-bit modes
- -40° to +85° C industrial temperature range
- 3.3V or 5V power input options
- Serial or parallel interfaces

Ordering Part #	Description	Approvals
MT9234SMI-92	V.92 Serial Data, V.34 Fax – 5V	Global
MT9234SMI-92-SP	V.92 Serial Data, V.34 Fax – 5V	Global
MT9234SMI-L-92	V.92 Serial Data, V.34 Fax – 3.3V	Global
MT9234SMI-L-92-SP	V.92 Serial Data, V.34 Fax – 3.3V	Global
MT9234SMI-HV-92	V.92 Serial Data, V.34 Fax – Medical - 5V	Global
MT9234SMI-HV-92-SP	V.92 Serial Data, V.34 Fax – Medical - 5V	Global
MT9234SMI-P-92	V.92 Parallel Data, V.34 Fax – 5V	Global
MT9234SMI-P-92-SP	V.92 Parallel Data, V.34 Fax – 5V	Global
MT9234SMI-P-L-92	V.92 Parallel Data, V.34 Fax – 3.3V	Global
MT9234SMI-P-L-92-SP	V.92 Parallel Data, V.34 Fax – 3.3V	Global
MT9234SMI-P-HV-92	V.92 Parallel Data, V.34 Fax – Medical - 5V	Global
MT9234SMI-P-HV-92-SP	V.92 Parallel Data, V.34 Fax – Medical - 5V	Global